

## EXTERNAL LINKS

HD67B20-5-B2



QR of Manual

---

[www.adfweb.com/download/  
filefold/MN67B20\\_ENG.pdf](http://www.adfweb.com/download/filefold/MN67B20_ENG.pdf)



QR of Box-Sheet

---

[www.adfweb.com/download/  
filefold/BS67B20-5-B2\\_ENG.pdf](http://www.adfweb.com/download/filefold/BS67B20-5-B2_ENG.pdf)



QR of Software

---

[www.adfweb.com/download/  
filefold/SW67B20.zip](http://www.adfweb.com/download/filefold/SW67B20.zip)

**HD67B20-5-B2**

# BOX SHEET

**OPC UA Client / NMEA 0183 - Converter**

Box Sheet for order code: HD67B20-5-B2  
Document code: BS67B20-5-B2  
V1.001





**ADFweb.com srl**  
Strada Nuova, 17, IT-31010 Mareno di Piave, Treviso - Italy


[www.ADFweb.com](http://www.ADFweb.com)

# CONNECTION SCHEME

Order code: HD67B20-5-B2

**Dip-Switch B:**  
-Dip1 – Termination RS485 line  
 = Open     = 120 ohm

**Dip-Switch A:**  
-Dip1 – Functioning Mode  
 = Normal Mode  
 = Boot Mode




**Led1:**  
Green  
Device state

**Led2:**  
Yellow  
OPC UA comm.


**Led3:**  
Yellow  
NMEA 0183 comm.

**Led4:**  
Yellow  
Error state



**Connector3:**  
Ethernet Port  
(RJ45 Plug)

**Led5:**  
Green  
Link Ethernet



**Connector4:**  
RS485 port  
S = Shield (to Isolated Ground)  
- = Negative wire  
+ = Positive wire

**Connector1:**  
Power Supply  
0V = Ground  
+V = Positive wire  
V AC: min 8V ; max 24V  
V DC: min 12V ; max 35V